

DECLARATION OF PERFORMANCE

Nr: CPR-2013-904-5

1. **Unique identification code of the product-type:**
Phono Spray S-904 /Isocianato H. PU EN14315-1-CCC1-CT4(22)-GT12(22)-TFT14(22)-FRC10(22)-W3,0-MU2
2. **Intended use/es:**
Thermal insulation for buildings
3. **Manufacturer:**
SYNTHESIA TECHNOLOGY EUROPE, S.L.U.
Argent,3 - 08755 Castellbisbal (Barcelona, Spain)
www.synthesia.com
5. **System/s of AVCP:**
AVCP- System 3 (RtF)
6. **Harmonised standard:**
EN 14315-1: 2013

Notified body/ies:
CEIS/Centro de ensayos, innovación y Servicios-Notified body Nr. 1722
FUNDACIÓN TECNALIA RESEARCH & INNOVATION - Notified body Nr. 1292
7. **Declared performance/s:**

ESSENTIAL CHARACTERISTICS		PERFORMANCE
Reaction to fire	Reaction to fire, Euroclasses	F
Water permeability	Short term water absorption by partial immersion ($W_p; Kg/m^2$)	3,00
Thermal resistance	Thermal resistance and thermal conductivity	See performance chart
Water vapour permeability	Water vapour transmission (μ)	2
Compressive strength	Compressive stress or compressive strength	NPD
Durability of reaction to fire against ageing/degradation	Durability characteristics	a
Durability of thermal resistance against ageing/degradation	Durability characteristics	b
Durability of compressive strength against ageing/degradation	Durability characteristics	c
Continuous glowing combustion	Continuous glowing combustion	d

^a The reaction to fire performance of PU products does not decrease with time.

^b The thermal resistance declared is determined with an ageing procedure.

^c The compression strength of PU products does not decrease with time.

^d No harmonised test method available.

PERFORMANCE CHART

Sprayed insulation foam product CCC1 system. Diffusion open faces.

e_p	35	40	45	50	55	60	65	70	75
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	0,90	1,05	1,15	1,30	1,45	1,55	1,70	1,85	1,95
e_p	80	85	90	95	100	105	110	115	120
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	2,10	2,25	2,35	2,50	2,60	2,75	2,90	3,00	3,15
e_p	125	130	135	140	145	150	155	160	165
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	3,30	3,40	3,55	3,70	3,80	3,95	4,10	4,20	4,35
e_p	170	175	180	185	190	195	200	205	210
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	4,50	4,60	4,75	4,85	5,00	5,15	5,25	5,40	5,55
e_p	215	220	225	230	235	240	245	250	255
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	5,65	5,80	5,95	6,05	6,20	6,35	6,45	6,60	6,75
e_p	260	265	270	275	280	285	290	295	300
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	6,85	7,00	7,15	7,25	7,40	7,50	7,65	7,80	7,90

e_p Thickness; mm

λ_D Declared aged thermal conductivity; (W/mK)

R_D Thermal resistance level; ($m^2 K/W$)

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufactured by:

At Barcelona on 23/05/2022



Juan Sánchez
Managing Director
Synthesia Technology Europe, S.L.U.