

# DECLARATION OF PERFORMANCE Nr: CPR-2013-907INC-3

#### 1. Unique identification code of the product-type:

Phono Spray S-907INC /Isocianato H. PU EN14315-1-CCC1-CT4(22)-GT9(22)-TFT12(22)-FRC43(22)-W3-MU5

#### 2. Intended use/es:

Thermal insulation for buildings

### 3. Manufacturer:

SYNTHESIA TECHNOLOGY EUROPE, S.L.U. Argent,3 - 08755 Castellbisbal (Barcelona, Spain) www.synthesia.com

# 5. System/s of AVCP:

AVCP- System 3 (4 RtF)

# 6. Harmonised standard:

EN 14315-1: 2013

## Notified body/ies:

CEIS/Centro de ensayos, innovación y Servicios-Notified body Nr. 1722 FUNDACIÓN TECNALIA RESEARCH & INNOVATION - Notified body Nr. 1292

### 7. Declared performance/s:

ESSENTIAL CHARACTERISTICS	PERFORMANCE		
Reaction to fire	Reaction to fire, Euroclasses	F	
Water permeability	Short term water absorption by partial immersion $(W_p; Kg/m^2)$	3,00	
Thermal resistance	Thermal resistance and thermal conductivity	See performance chart	
Water vapour permeability	Water vapour transmission (μ)	5	
Compressive strength	Compressive stress or compressive strength	NPD	
Durability of reaction to fire against ageing/degradation	Durability characteristics	ā	
Durability of thermal resistance against ageing/degradation	Durability characteristics	b	
Durability of compressive strength against ageing/degradation	Durability characteristics	c	
Continuous glowing combustion	Continuous glowing combustion	d	

 $<sup>\</sup>overline{\ }^a$  The reaction to fire performance of PU products does not decrease with time.

<sup>&</sup>lt;sup>b</sup> The thermal resistance declared is determined with an ageing procedure.

 $<sup>^{\</sup>rm c}\,$  The compression strength of PU products does not decrease with time.

<sup>&</sup>lt;sup>d</sup> No harmonised test method available.



# PERFORMANCE CHART

Sprayed insulation foam product CCC1 system. Diffusion open faces.

e <sub>p</sub>	10	15	20	25	30	35	40	45	50
$\lambda_{D}$	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
$R_D$	0,25	0,35	0,50	0,65	0,75	0,90	1,05	1,15	1,30

e p Thickness; mm

 $\lambda_D$  Declared aged thermal conductivity; (W/mK)

 $R_D$  Thermal resistance level; (m  $^2$ K/W)

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufactured by:

At Barcelona on 19/03/2021

Thomas Christensen Managing Director

Synthesia Technology Europe, S.L.U.

V. Chilense