

## DECLARATION OF PERFORMANCE

**Nr: CPR-2021-351C HFO-3**

1. **Unique identification code of the product-type:**  
Poliuretán Spray RF-351C HFO/Isocianato H. PU EN14315-1-CCC4-CT4(22)-GT7(22)-TFT8(22)-FRB37(22)-W0,2-MU50
2. **Intended use/es:**  
Thermal insulation for buildings
3. **Manufacturer:**  
SYNTHESIA TECHNOLOGY EUROPE, S.L.U.  
Argent,3 - 08755 Castellbisbal (Barcelona-España)  
[www.synthesia.com](http://www.synthesia.com)
5. **System/s of AVCP:**  
AVCP- System 1  
AVCP- System 3
6. **Harmonised standard:**  
EN 14315-1: 2013

**Notified body/ies:**

Asociación Española de Normalización y Certificación (AENOR)-Notified body Nr 0099  
CEIS/Centro de ensayos, innovación y Servicios-Notified body Nr. 1722  
AFITI/ Asociación para el Fomento de la Investigación y la Tecnología de la Seguridad contra Incendios - Notified body Nr. 1168

7. **Declared performance/s:**

ESSENTIAL CHARACTERISTICS		PERFORMANCE
Reaction to fire	Reaction to fire, Euroclasses	C-s3,d0
Water permeability	Short term water absorption by partial immersion ( $W_p; Kg/m^2$ )	0,20
Thermal resistance	Thermal resistance and thermal conductivity	See performance chart
Water vapour permeability	Water vapour transmission ( $\mu$ )	50
Compressive strength	Compressive stress or compressive strength	CS(10\Y)200
Durability of reaction to fire against ageing/degradation	Durability characteristics	a
Durability of thermal resistance against ageing/degradation	Durability characteristics	b
Durability of compressive strength against ageing/degradation	Durability characteristics	c
Continuous glowing combustion	Continuous glowing combustion	d

<sup>a</sup> The reaction to fire performance of PU products does not decrease with time.

<sup>b</sup> The thermal resistance declared is determined with an ageing procedure.

<sup>c</sup> The compression strength of PU products does not decrease with time.

<sup>d</sup> No harmonised test method available.

## PERFORMANCE CHART

*Sprayed insulation foam product CCC4 system. Diffusion open faces.*

$e_p$	<b>25</b>	<b>30</b>	<b>35</b>	<b>40</b>	<b>45</b>	<b>50</b>	<b>55</b>	<b>60</b>	<b>65</b>
$\lambda_D$	0,028	0,028	0,028	0,028	0,028	0,028	0,028	0,028	0,028
$R_D$	0,90	1,10	1,25	1,45	1,65	1,85	2,00	2,20	2,40
$e_p$	<b>70</b>	<b>75</b>	<b>80</b>	<b>85</b>	<b>90</b>	<b>95</b>	<b>100</b>	<b>105</b>	<b>110</b>
$\lambda_D$	0,028	0,028	0,026	0,026	0,026	0,026	0,026	0,026	0,026
$R_D$	2,55	2,75	3,10	3,25	3,45	3,65	3,85	4,05	4,25
$e_p$	<b>115</b>	<b>120</b>	<b>125</b>	<b>130</b>	<b>135</b>	<b>140</b>	<b>145</b>	<b>150</b>	
$\lambda_D$	0,026	0,025	0,025	0,025	0,025	0,025	0,025	0,025	
$R_D$	4,45	4,80	5,00	5,20	5,40	5,60	5,80	6,00	

$e_p$  Thickness; mm

$\lambda_D$  Declared aged thermal conductivity; (W/mK)

$R_D$  Thermal resistance level; ( $m^2 K/W$ )

***The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.***

***Signed for and on behalf of the manufactured by:***

At Barcelona on 23/12/2021



Thomas Christensen  
Managing Director  
Synthesia Technology Europe, S.L.U.