

DECLARATION OF PERFORMANCE

Nr: CPR-2024-OC007-2

1. Unique identification code of the product-type:

Poliuretán Spray S-OC-007 / Isocianato H. PU EN14315-1-CCC1-CT5(22)-GT12(22)-TFT14(22)-FRC7,5(22)-W5-MU2

2. Intended use/es:

Thermal insulation for buildings

3. Manufacturer:

SYNTHESIA TECHNOLOGY EUROPE, S.L.U.

Argent,3 - 08755 Castellbisbal (Barcelona-Spain)

www.synthesia.com

5. System/s of AVCP:

AVCP- System 3

6. Harmonised standard:

EN 14315-1: 2013 + NB-CPR/SG19-22/213r1 (12/12/2022)

Notified body/ies:

CEIS/Centro de ensayos, innovación y Servicios-Notified body Nr. 1722

LGAI TECHNOLOGICAL CENTER, S.A/APPLUS - Notified body Nr. 0370

7. Declared performance/s:

ESSENTIAL CHARACTERISTICS		PERFORMANCE
Reaction to fire	Reaction to fire, Euroclasses	E
Water permeability	Short term water absorption by partial immersion (Wp; Kg/m2)	≤ 5
Thermal resistance	Thermal resistance and thermal conductivity	See performance chart
Water vapour permeability	Water vapour transmission (μ)	≥ 2
Compressive strength	Compressive stress or compressive strength	NPD
Durability of reaction to fire against ageing/degradation	Durability characteristics	a
Durability of thermal resistance against ageing/degradation	Durability characteristics	b
Durability of compressive strength against ageing/degradation	Durability characteristics	c
Continuous glowing combustion	Continuous glowing combustion	d

a The reaction to fire performance of PU products does not decrease with time.

b The thermal resistance declared is determined with an ageing procedure.

c The compression strength of PU products does not decrease with time.

d No harmonised test method available.

PERFORMANCE CHART

Sprayed insulation foam product CCC1 system. Diffusion open faces.

e_p	35	40	45	50	55	60	65	70	75
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	0,90	1,05	1,15	1,30	1,40	1,55	1,70	1,80	1,95
e_p	80	85	90	95	100	105	110	115	120
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	2,10	2,20	2,35	2,50	2,60	2,75	2,85	3,00	3,15
e_p	125	130	135	140	145	150	155	160	165
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	3,25	3,40	3,55	3,65	3,80	3,95	4,05	4,20	4,30
e_p	170	175	180	185	190	195	200	205	210
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	4,45	4,60	4,70	4,85	5,00	5,10	5,25	5,40	5,50
e_p	215	220	225	230	235	240	245	250	255
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	5,65	5,75	5,90	6,05	6,15	6,30	6,45	6,55	6,70
e_p	260	265	270	275	280	285	290	295	300
λ_D	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038	0,038
R_D	6,85	6,95	7,10	7,20	7,35	7,50	7,60	7,75	7,90

e_p Thickness; mm
 λ_D Declared aged thermal conductivity; (W/mK)
 R_D Thermal resistance level; (m²K/W)

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufactured by:

At Barcelona on 18/06/2025



Davidalleja
 CEO
 Synthesia Technology Europe, S.L.U