

## DECLARATION OF PERFORMANCE

Nr: CPR-2013-OC008-9

**1. Unique identification code of the product-type:**

Poliuretán Spray S-OC-008/Isocianato H

**2. Intended use/es:**

Thermal insulation for buildings

**3. Manufacturer:**

SYNTHESIA TECHNOLOGY EUROPE, S.L.U.

Argent,3 - 08755 Castellbisbal (Barcelona-Spain)

[www.synthesia.com](http://www.synthesia.com)

**5. System/s of AVCP:**

AVCP- System 3

**6. Harmonised standard:**

EN 14315-1: 2013

**Notified body/ies:**

CEIS/Centro de ensayos, innovación y Servicios-Notified body Nr. 1722

LGAI TECHNOLOGICAL CENTER, S.A/APPLUS - Notified body Nr. 0370

**7. Declared performance/s:**

ESSENTIAL CHARACTERISTICS		PERFORMANCE
Reaction to fire	Reaction to fire, Euroclasses	F
Water permeability	Short term water absorption by partial immersion (Wp; Kg/m <sup>2</sup> )	5,0
Thermal resistance	Thermal resistance and thermal conductivity	See performance chart
Water vapour permeability	Water vapour transmission (μ)	2
Compressive strength	Compressive stress or compressive strength	NPD
Durability of reaction to fire against ageing/degradation	Durability characteristics	a
Durability of thermal resistance against ageing/degradation	Durability characteristics	b
Durability of compressive strength against ageing/degradation	Durability characteristics	c
Continuous glowing combustion	Continuous glowing combustion	d

a The reaction to fire performance of PU products does not decrease with time.

b The thermal resistance declared is determined with an ageing procedure.

c The compression strength of PU products does not decrease with time.

d No harmonised test method available.

## PERFORMANCE CHART

Sprayed insulation foam product CCC1 system. Diffusion open faces.

<b>e<sub>p</sub></b>	<b>35</b>	<b>40</b>	<b>45</b>	<b>50</b>	<b>55</b>	<b>60</b>	<b>65</b>	<b>70</b>	<b>75</b>
λ <sub>D</sub>	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039
R <sub>D</sub>	0,90	1,00	1,15	1,30	1,40	1,55	1,70	1,80	1,95
<b>e<sub>p</sub></b>	<b>80</b>	<b>85</b>	<b>90</b>	<b>95</b>	<b>100</b>	<b>105</b>	<b>110</b>	<b>115</b>	<b>120</b>
λ <sub>D</sub>	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039
R <sub>D</sub>	2,05	2,20	2,35	2,45	2,60	2,75	2,85	3,00	3,10
<b>e<sub>p</sub></b>	<b>125</b>	<b>130</b>	<b>135</b>	<b>140</b>	<b>145</b>	<b>150</b>	<b>155</b>	<b>160</b>	<b>165</b>
λ <sub>D</sub>	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039
R <sub>D</sub>	3,25	3,40	3,50	3,65	3,80	3,90	4,05	4,15	4,30
<b>e<sub>p</sub></b>	<b>170</b>	<b>175</b>	<b>180</b>	<b>185</b>	<b>190</b>	<b>195</b>	<b>200</b>	<b>205</b>	<b>210</b>
λ <sub>D</sub>	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039
R <sub>D</sub>	4,45	4,55	4,70	4,85	4,95	5,10	5,20	5,35	5,50
<b>e<sub>p</sub></b>	<b>215</b>	<b>220</b>	<b>225</b>	<b>230</b>	<b>235</b>	<b>240</b>	<b>245</b>	<b>250</b>	<b>255</b>
λ <sub>D</sub>	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039
R <sub>D</sub>	5,60	5,75	5,90	6,00	6,15	6,25	6,40	6,55	6,65
<b>e<sub>p</sub></b>	<b>260</b>	<b>265</b>	<b>270</b>	<b>275</b>	<b>280</b>	<b>285</b>	<b>290</b>	<b>295</b>	<b>300</b>
λ <sub>D</sub>	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039	0,039
R <sub>D</sub>	6,80	6,95	7,05	7,20	7,30	7,45	7,60	7,70	7,85

- e<sub>p</sub> Thickness; mm
- λ<sub>D</sub> Declared aged thermal conductivity; (W/mK)
- R<sub>D</sub> Thermal resistance level; (m2K/W)

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufactured by:

At Barcelona on 21/11/2022



Davidalleja  
CEO  
Synthesia Technology Europe, S.L.U